

5. CAUTION

- HEAT KILLS BATTERIES. YOU MUST AVOID PLACING BATTERIES IN CLOSE PROXIMITY TO HEAT SOURCES OF ANY KIND.
YOU WILL ENJOY LONGER SERVICE LIFE. IF BATTERIES ARE OPERATED IN AMBIENT TEMPERATURE RANGE OF 20°C (68°F) TO 25°C (77°F)
- SINCE THE BATTERIES MAY GENERATE IGNITABLE GAS, PLEASE DO NOT INSTALL THEM CLOSE TO ANY ITEM THAT PRODUCES SPARKS.
- IF THE BATTERY IS TO BE USED IN A CLOSED SPACE OR IN A CONTAINER, PROVISION SHOULD BE MADE FOR ADEQUATE VENTILATION.
- AS THE BATTERY CONTAINERS AND COVERS ARE MADE OF ABS720 RESIN, PLACING BATTERIES IN AN ATMOSPHERE OF, OR IN CONTACT WITH ORGANIC SOLVENTS OR ADHESIVE MATERIAL SHOULD BE AVOIDED.
- USE SHOCK ABSORBER AND FASTEN BATTERY FIRMLY WHEN HEAVY VIBRATION OR EXPECTED DURING SERVICE.
- CLEAN THE BATTERY WITH A PIECE OF WET CLOTH. NEVER HAVE THE BATTERY SPLASHED OR DEPOSITED WITH OILS OR ORGANIC SOLVENTS SUCH AS GASOLINE OR PAINT THINNER, NOR HAVE IT CLEANED WITH CLOTHS IMPERMANENT WITH THESE MATERIALS.
- DISMANTLING THE BATTERY IS NOT ADVISABLE. IF SULFURIC ACID IS DEPOSITED ON SKIN OR CLOTHES, PLEASE WASH WELL WITH SUFFICIENT AMOUNT OF FRESH WATER AND OBTAIN IMMEDIATE MEDICAL ATTENTION.
- A BATTERY IS LIABLE TO RUPTURE IF THROWN INTO FIRE.
PLEASE AVOID SUCH CONDUCT AT ALL TIMES.
- TOUCHING ELECTRICALLY CONDUCTIVE PARTS MIGHT RESULT IN AN ELECTRIC SHOCK. BE SURE TO WEAR RUBBER GLOVES BEFORE INSPECTION OR REGULAR SERVICE.
- MIXED USE OF BATTERIES WITH DIFFERENT CAPACITIES, HISTORIES AND/OR MANUFACTURES IS LIABLE TO CAUSE DAMAGE TO THE BATTERY OR THE EQUIPMENT. IF THIS IS UNAVOIDABLE PLEASE CONSULT MANUFACTURER BEFOREHAND. DO NOT SHORT CIRCUIT THE BATTERY, AS IT CAN BURN OUT THE CONNECTIONS AND COULD DAMAGE EQUIPMENT.
- TO OBTAIN MAXIMUM LIFE, BATTERIES SHOULD NEVER BE STORED IN A DISCHARGED STATE. BE SURE TO RECHARGE THE BATTERY AFTER DISCHARGING.